www.maharnet.com

Q





How To Change WiFi Password

YGN Hot line : 09770333373

MDY Hot line : 09770333383

ONU Model - HG8546M

အဆင့်(၁) - မိမိဖုန်းမှ wifi ကိုဖွင့်ပြီး သက်ဆိုင်ရာ wifi name သို့ချိတ်ဆက်ပါ



ပုံ(၁)Wifi စတင်ဖွင့်လျှင်ပေါ်သည့်ပုံ



စာမျက်နှာ ၁/၆



<mark>အဆင့်(၂)-မိမိဖုန်းမှ</mark> Browser <mark>သို့သွားပါ</mark> Browser <mark>တွင် 192.168.100.1</mark> ကိုရိုက်ထည့်ပါ



10:35 AM (© I) ເພີ້ອມປະປະທ No internet connection Browser တွင် 192.168.100.1 ເພື່ອ HG8546M 192.168.100.1 9 192.168.100.1

ပုံ(၄)Browserတွင် 192.168.100.1 ရိုက်ထည့်ထားသည့်ပုံ



Browser တွင် 192.168.100.1ရိုက်ထည့်ပြီး ONU Login page ပေါ်လာပါလိမ့်မည် ထိုသို့ပေါ်လာပါက username တွင် <mark>root</mark> ကိုရိုက်ပါ password တွင် <mark>adminHW</mark> ကိုရိုက်ပြီ<mark>း login Box</mark> ကိုနှိပ်ပါ

```
ပုံ(၅)ONU Login page ပေါ်လာပုံ
```

ပုံ(၆)User name နှငို Password ရိုက်ထည့်ထားသည့်ပုံ



စာမျက်နှာ ၄/၆

အဆင့်(၃)Login ကိုနှိပ်ပြီးပါက ONU ထဲသို့ရောက်ရှိသွားပါမည် ထိုသို့ပေါ်လာပြီးပါက WLAN Tag သို့သွားပါ

ບໍ (WLAN tag		ပုံ(၈) Page မှ WLAN tag သို့ ဝင်ထားသည့်ပုံ							
C A https://10.204.7.9:	80/index.asp		Logout	HUAWEI	HG854 Status WAN	6M LAN IPv6 WLAN Secur	ity Route Forward	Rules Network Applicatio	n Voice System	Logout
HUAWEI Status WAI	N LAN IPv6 WLAN Securi	ity Route Forward Rules Network Application Voice System Too	ls	WLAN Basic Configu WLAN Advanced Con	ration '	WLAN > WLAN Basic Configura	tion			_
VAN Information	Status > Device Information On this page, you can view t	basic device information.		Automatic WiFi Shute WiFi Coverage Manag	Jown gement	On this page, you can set b: Caution: 1. Wireless network service 2. It is recommended that you	asic WLAN parameter s may be interrupted t ou use the WPA2 or W	s(When the WLAN function i emporarily after you modify \ PA/WPA2 authentication mo	s disabled, this pag vireless network pa le for security purpo	e is blank). rameters. Ises.
th Port Information	Device Type:	HG8546M				🗹 Enable WLAN				New Delete
HCP Information Dptical Information	Description:	EchoLife HG8546M GPON Terminal (CLASS B+/PRODUCT ID:2150083733EGJB237781/CHIP:00050020170909)				SSID Index SSID Name	e SSID Status Nur Enabled 32	nber of Associated Devices	Broadcast SSI	D Security Configuration Configured
Device Information	SN:	48575443265AE792 (HWTC265AE792)				SSID Configuration Details				
Remote Manage	Hardware Version:	10C7.A				SSID Name:	Ko Kan Cho	* (1-32 characters)		
Jser Device Information	Software Version:	V3R017C10S125				Enable SSID:				
Service Provisioning Status	Manufacture Info:	2150083733EGJB237781.C412				Devices:	32	* (1-32)		
	ONT Registration Status:	O5(Operation state)				Broadcast SSID:				
	ONTID:	46				Enable WMM:				
	CPU Usage:	12%				Authentication Mode:	WPA/WPA2 PreSI	naredKey 🗸		
	Memory Usage:	34%				Encryption Mode:	TKIP&AES	v]		
	Custom Into:					WPA PreSharedKey:	•••••	Hide * (8-63 char;	acters or 64 hexade	cimal characters)
	The administrator uses the ir	2000-04- 14 22:38:39+06:30 nitial password. If you want to change this password, please contact the te	elecom carrier. For			WPA Group Key Regeneration	3600	*(600-86400s)		
	details about how to change	the password, see the Security Maintenance from http://support.huawei.co	om.			Enable WPS:				

စာမျက်နှာ ၅/၆

အဆင့်(၄)WLAN Tag ထဲမှ WPA PreSharedKey Box ထဲတွင် မိမိchange လိုသော password ကိုထည့်ပါ ထို့နောက် <mark>Apply</mark> button အားနှိပ်ပါ

Password ထည့်ရမည့်နေရာ

ပုံ(၉)change လိုသော password ရိုက်ထည့်ထားသည့်ပုံ

- 仚
- ▲ 192.168.100.1/index.as; 5

temporarily after you modify wireless network parameters.

2. It is recommended that you use the WPA2 or WPA/WPA2 authentication mode for security purposes.

Enable WLAN

1	HUAWEI-8ec0	Enabled	32			Enabled	Configured	
SID Configuratio	n Details							
SSID Name:		HUAWEI-8ec0 (1-32 characters)						
Enable SSID:								
Number of Associated Devices:		32 * (1-32)						
Broadcast SSID:								
Enable WMM:		Z						
Authentication M	ode:	WPA/WPA2	PreShared	Key 🗸				
Encryption Mode:		TKIP&AES						
WPA PreSharedKey:		Hide * (8-63 characters or 64 hexadecimal characters)						
WPA Group Key Regeneration Interval:		3600 *(600-86400s)						
Enable WPS:								
WPS Mode:		(PBC V)						
PBC:		Staft WPS						
		Apply Can	cel					

ပုံ(၁၀)Apply button နှိပ်ထားသည့်ပုံ

合

▲ 192.168.100.1/index.ast 5

:

temporarily after you modify wireless network parameters. 2. It is recommended that you use the WPA2 or WPA/WPA2 authentication mode for security purposes.

Enable WLAN

New Delete Security Configuration SSID Index SSID Name SSID Status Number of Associated Devices Broadcast SSID 1 HUAWEI-8ec0 Enabled 32 Enabled Configured SSID Configuration Details SSID Name HUAWEI-8ec0 * (1-32 characters) ~ Enable SSID: Number of Associated Devices: 32 * (1-32) ~ Broadcast SSID ~ Enable WMM: Authentication Mode: WPA/WPA2 PreSharedKey V Encryption Mode: TKIP&AES WPA PreSharedKey: Hide * (8-63 characters or 64 hexadecimal characters) WPA Group Key Regeneration 3600 *(600-86400s) Interval: **Apply Button** Enable WPS PBC WPS Mode PBC: Apply Cancel 50 Copyright © Huawei Technologies Co., Ltd. 2020-2030. All rights reserved.

စာမျက်နှာ ၆/၆

Apply နှိပ်ပြီးပါကPage ညာဘက်ထောင့်ရှိ logoutကိုနှိပ်ပြီး ONU ထဲမှပြန်ထွက်ပါ ထို့နောက်မိမိဖုန်းမှ Wi-Fi ကို ပြန်လည်ချိတ်ဆက်ကြည့်ပါ Password အသစ်တောင်းပါလိမ့် မည် အသစ်changeလိုက်သောpassword ကိုရိုက်ထည့်ပြီး Password အသစ်ဖြင့် Internet အသုံးပြုနိုင်ပါပြီ

ပုံ(၁၁)Logout button နှိပ်ထားသည့်ပုံ



ပုံ(၁၂)Logout ထွက်သွားပြီးမြင်တွေ့ရသည့်ပုံ